

IMEX DSS2 Accessories



The default DSS2 station is equipped with Pro-Face PLC and painted frame.

Full stainless steel frame and Siemens PLC are optional.

Packaging: Wooden crate with special treatment NIMP.

Available accessories:

Solvent pen for rinsing
(\varnothing 2 / \varnothing 2,5 / \varnothing 3 mm)
Other diameters or solvent dispersing gun on request.



PEHD plastic sheet with stainless steel bowl for Ultrasonic
(load max. 10 kg; holes \varnothing 15 mm; thickness 15 mm)



Cascade membrane holder with easy opening
No risk to generate additional contamination.
Maximum 3 membranes.
Opening by lever.



2 stainless steel folded bars
(\varnothing 14 mm; load max. 25 Kg)



Kompetencia és tapasztalat

IMEX DSS2 Accessories

Electro polished stainless steel grid
(270 x 270 mm; inner twigs 3&6 mm; load max. 10 Kg)



Polished bowl with integrated membrane holder
for very small parts
Vacuum cut off manual valve.
Connection to the port A.
Installed under clean room.



PEHD plastic sheet
(load max. 10 kg; holes Ø 15 mm; thickness 15 mm)



Solvent filling up set with quick connector and filter
Connection to the port A.



Other accessories available on request.



Recommended consumables:

- Nylon analysis filtration membrane, 47 diameter - 5 µm, box of 100 units. (NCG047100)
- Filter element for the solvent – Solvent pen and walls fluid circuits. (SLK7002NAP)
- Pre filter for the laminar flow inlet.
- Filter housing installed at the top of the solvent tank. (KA1J100P1)